

Model: C1375D5

Powered by CUMMINS

Output Rating

MODEL	Power rating		Voltage available
	PRIME(1)	STANDBY(2)	
C1375D5	400V/50HZ	1000KW 1250KVA	1100KW 1375KVA
	PF:0.8		


General Information

Model	C1375D5
Engine	KTA50G3
Speed control type	Electronic
Phase	3
Control System	Digital
System voltage	24V
Frequency	50HZ
Engine Speed(RPM)	1500
Fuel Consumption L/hr	Standby power(2) Prime Power(1) 75% prime power 50% prime power
	293 274 161 199



Dimension and Weight

Dimension	Open	Silent
Length(L)	4950mm	12190mm
Width (W)	2060 mm	2438mm
Height (H)	2250mm	2896mm
Net Weight	9600KG	21200KG



AGG POWER gensets are compliant with EC mark which include the following directives:

- * 2006/42/EC Machinery safety.
- * 2006/95/EC Low voltage
- * EN 60204-1: 2006+A1:2009, EN ISO 12100:2010, EN ISO 13849-1: 2008, EN 12601: 2010

(1) Prime Power(PR):

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operation conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24h of operation shall not exceed 70% of the PR.

(2) Standby Power (ESP):

According to ISO 8528-1:2005, standby power is the maximum power available during a variable electrical power sequence, under the stated operation conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24h of operation shall not exceed 70% of the ESP.



▪ Engine Specification

GENERAL ENGINE DATA

Type 4-Cycle; 60° Vee; 12-Cylinder Diesel
 Aspiration Turbocharged and Aftercooled
 Bore x Stroke in x in (mm x mm) 6.25x 6.25 (159 x 159)
 Displacement - in.3(L) 3067 (50.3)
 Compression Ratio 14.9:1

Dry Weight

--Fan to Flywheel Engine - lb. (kg)..... 11820(5360)

Wet Weight

--Fan to Flywheel Engine - lb. (kg).....12485(5662)

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Block lb *ft²(N*m) 4500 (6100)

EXHAUST SYSTEM

Maximum Back Pressure @ Standby Power Rating — in Hg (mm Hg) 2(51)

AIR INDUCTION SYSTEM

Maximum Intake Air Restriction
with Dirty Filter Element..... in H₂O (mm H₂O) 25 (635)
with Clean Filter Elementin H₂O(mm H₂O) 15(381)

COOLING SYSTEM

Coolant Capacity — Engine Only	— US gal (liter) 37 (140)
— Aftercoolers.....	— US gal (liter) 9 (34)
Maximum Static Head of Coolant Above Engine Crank Centerline.....	— ft (m) 60 (18.3)
Thermostat Modulating Range — High Flow (Jacket)	— °F (°C) 180 - 200 (82 - 93)
Maximum Top Tank Temperature for Standby Power / Prime Power.....	— °F (°C) 220 / 212 (104 / 100)
Target Coolant Inlet Temperature to Aftercoolers @ 77 °F (25 °C) Ambient—	— °F (°C) 130 (55)
Maximum Coolant Temperature to Aftercoolers; Standby Power / Prime Power	— °F (°C) 160 / 150 (71 / 66)

LUBRICATION SYSTEM

Oil Pressure @ Idle Speed — psi (kPa) 20 (138)
 @ Governed Speed — psi (kPa) 50 - 70 (345 - 483)
 Maximum Oil Temperature — °F (°C) 250 (121)
 Oil Capacity with OP 6027 Oil Pan : High - Low — US gal (liter) 47 - 39 (178 - 148)
 Total System Capacity (Including Bypass Filter) — US gal (liter) 54 (204)

FUEL SYSTEM

ELECTRICAL SYSTEM

Cranking Motor (Heavy Duty, Positive Engagement).....	volt 24
Battery Charging System, Negative Ground.....	--- ampere 35
Maximum Allowable Resistance of Cranking Circuit.....	ohm 0.002
Minimum Recommended Battery Capacity	
-Cold Soak @ 50 °F(10°C) and Above.....	0 °F CCA 1200
Cold Soak @ 32°Fto 50 °C (0 °C to 10°C).....	0 °F CCA 1280
-Cold Soak @ 0 °F to 32 °C (-18 °C to 0 °C).....	0 °F CCA1800



▪ Alternator

Alternator		
Poles	Num	4
Winding Connections (standard)		Star-serie
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Exciter System		Brushless
Voltage Regulator		A.V.R. (Electronic)
Bearing		Single bearing
Coupling		Flexible disc
Coating type		Standard (Vacuum impregnation)

▪ Options

Engine	Alternator	Generator Sets	Fuel System	Canopy
<ul style="list-style-type: none"> • Water Jacket Preheater • Oil Preheater 	<ul style="list-style-type: none"> • Winding Temperature measuring Instrument • Alternator Preheater • PMG • Anti-damp and anti-corrosion treatment • Anti-condensation heater 	<ul style="list-style-type: none"> • Tools with the machine 	<ul style="list-style-type: none"> • Low fuel level alarm • Automatic fuel feeding system • Fuel T-valves 	<ul style="list-style-type: none"> • Rental Type Canopy • Trailer
Lubricating System	Exhaust System	Cooling System	Control Panel	Voltages
<ul style="list-style-type: none"> • Oil with the machine 	<ul style="list-style-type: none"> • Protection board from hotness 	<ul style="list-style-type: none"> • Front heat protection • Coolant (-30°C) 	<ul style="list-style-type: none"> • Remote control panel • ATS • Remote controller • Synchronizing controller 	<ul style="list-style-type: none"> • 415/240V • 380/220V • 220/127V • 220/127V • 200-115V



▪ Control Panel



Available extension modules

Product	Description	Order code
CM-Ethernet	Ethernet interface	CM2ETHERBX
CM-GPRS	GSM modem / wireless internet	CM2GPRSXXBX
CM-RS232-485	Dual port interface	CM223248BX
EM-BIO8-EFCP	8 additional binary inputs/outputs	EM2BIO8EXBX

Functions and protections

Description	ANSI code	Description	ANSI code
Over voltage	59	Load shedding	32P
Under voltage	27	Overload	32
Voltage asymmetry and Phase rotation**	47	Power factor	55
Over frequency	81H	Temperature	49T
Under frequency	81L	Gas (fuel) level	71
Over current*	50 + 51	Earth fault current	50N + 64
Current unbalance	46		

* Short current only

** Fixed setting

Product description

- Single gen-set controller for Stand-by and Prime-power applications
- Direct communication with EFI engines
- Total remote monitoring and control

Key features

- Easy to install, configure and use
- Wide range of communication capabilities including:
 - connection via RS232, RS485, CAN and on board USB
 - internet access using Ethernet or GPRS
 - support for Modbus and SNMP protocols
- Cloud-based monitoring and control
- Active SMS and emails in different languages
- 2x 5 A binary outputs for cranking and fuel solenoid
- Option for up to 16 additional binary inputs/outputs
- Flexible event based history with up to 350 events
- Load shedding, dummy load capability
- Automatic temperature based cooling/heating
- Comprehensive gen-set protections
- Multipurpose flexible timers
- True RMS measurement

