

## Model: P800D5

Powered by PERKINS

### Output Rating

MODEL		Power rating		Voltage available		
		PRIME(1)	STANDBY(2)			
P800D5	400V/50HZ	580KW	640KW	380/220V	400/230V	415/240V
	PF:0.8	725KVA	800KVA			


### General Information

Model	P800D5		
Engine	4006-23TAG2A		
Speed control type	Electronic		
Phase	3		
Control System	Digital		
System voltage	12V/24V		
Frequency	50HZ		
Engine Speed(RPM)	1500		
Fuel Consumption L/hr	Standby power(2)	178	
	Prime Power(1)	163	
	75% prime power	124	
	50% prime power	84	



### Dimension and Weight

Dimension	Open	Silent
Length (L)	4320mm	6050mm
Width (W)	1730mm	2438mm
Height (H)	2180mm	2591mm
Net Weight	5413KG	12700KG



AGG POWER gensets are compliant with EC mark which include the following directives:

- \* 2006/42/EC Machinery safety.
- \* 2006/95/EC Low voltage
- \* EN 60204-1: 2006+A1:2009, EN ISO 12100:2010, EN ISO 13849-1: 2008, EN 12601: 2010

#### (1) Prime Power (PRP):

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operation conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24h of operation shall not exceed 70% of the PRP.

#### (2) Standby Power (ESP):

According to ISO 8528-1:2005, standby power is the maximum power available during a variable electrical power sequence, under the stated operation conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24h of operation shall not exceed 70% of the ESP.



## Engine Specification

### Basic technical data

Number of cylinders .....6  
 Cylinder arrangement ..... Vertical, In line  
 Cycle ..... 4 stroke, compression ignition  
 Induction system ..... Turbocharged  
 Compression ratio ..... 13.6:1 nominal  
 Bore ..... 160 mm  
 Stroke ..... 190 mm  
 Cubic capacity ..... 22,921 litres  
 Direction of rotation ..... Anti-clockwise viewed on flywheel  
 Firing order ..... 1, 5, 3, 6, 2, 4  
 Cylinder 1 ..... furthest from flywheel  
 Total weight of Electrounit (engine only)  
 -dry ..... 2524 kg  
 -wet ..... 2663 kg

### Overall dimensions

-height ..... 1964 mm  
 -length ..... 3027 mm  
 -width ..... 1706 mm

### Moment of inertia

Engine ..... 4.59 kgm<sup>2</sup>  
 Flywheel ..... 6.02 kgm<sup>2</sup>  
 Cyclic irregularity for engine/flywheel (prime power):

### Cooling system

Recommended coolant: 50% inhibited ethylene glycol or 50% inhibited propylene glycol and 50% clean fresh water. For combined heat and power systems and where there is no likelihood of ambient temperature below 10 °C, then clean 'soft' water may be used, treated with 1% by volume of Perkins inhibitor in the cooling system. The inhibitor is available in 1 litre bottles from Perkins.  
 Nominal jacket water pressure in crankcase. .... 170 kPa  
 Maximum top temperature (standby) ..... 98 °C  
 Maximum static pressure head on pump ..... 7 m  
 Draw down capacity ..... 22 litres  
 Maximum permissible restriction to coolant pump flow ..... 20 kPa  
 Thermostat operating range ..... 71 - 85 °C  
 Ambient cooling clearance (open ElectropaK prime power) based on air temp at fan 3 °C above ambient.

### Radiator

Face area ..... 2,569 m<sup>2</sup>  
 Rows and materials ..... 3 rows of brass tubes

### Gills per inch and material

-jacket water ..... Copper fin at 14 gills/in  
 -charge air section ..... Copper fin at 10 gills/in

### Width and height of matrix

-height ..... 1600 mm  
 -width ..... 1606 mm  
 Weight (dry) radiator ..... 570 kg  
 Total coolant capacity ..... 105 litres  
 Pressure cap setting ..... 70 kPa

### Exhaust system

Exhaust outlet size (internal) ..... 2 x 152,4 mm

### Exhaust back pressure for total system

-TAG2A ..... 610 mm H<sub>2</sub>O

### Lubrication system

Recommended lubricating oil to conform with the specification of API CG4 15W/40

### Lubricating oil capacity

-sump maximum ..... 113,4 litres  
 -sump minimum ..... 90,7 litres

### Lubrication oil pressure at rated speed

Minimum ..... 240 kPa  
 Oil relief values open ..... 300 kPa  
 Oil filter spacing ..... 40 microns  
 Sump drain plug tapping size ..... G1  
 Oil pump speed and method of drive ..... 1.4 x e rev/min, gear

## General installation

### 4006-23TAG2A - Temperate

Designation	Units	50 Hz 1500 rev/min			60 Hz 1800 rev/min		
		Baseload power	Prime power	Standby power	Baseload power	Prime power	Standby power
Gross engine power	kWm	527	654	717	549	676	740
Fan power	kWm	22			38		
Net engine power	kWm	505	632	695	511	638	702
BMEP gross	kPa	1840	2281	2502	1597	1966	2152
Combustion air flow	m <sup>3</sup> /min	60	64	71	62	65	72
Exhaust gas temperature max. after turbo	°C	430					
Exhaust gas flow (max)	m <sup>3</sup> /min	180			190		
Boost pressure ration	-	3,0	3,4	3,6	3,2	3,4	3,6
Mechanical efficiency	%	90					
Overall thermal efficiency	%	43	42	41	41,5	41	40
Friction power and pumping losses	kWm	70			75		
Mean piston speed	m/s	9,5			11,4		
Engine coolant flow	l/s	10			12		
Cooling fan airflow	m <sup>3</sup> /min	1200			1320		
Typical Genset electrical output 0.8pf 25 °C (100 kPa)	kVA	600	750	825	600	750	825
	kWe	480	600	660	480	600	660
Assumed alternator efficiency	%	95			94		



## ▪ Alternator

Alternator		
Poles	Num	4
Winding Connections (standard)		Star-serie
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Exciter System		Brushless
Voltage Regulator		A.V.R. (Electronic)
Bearing		Single bearing
Coupling		Flexible disc
Coating type		Standard (Vacuum impregnation)

## ▪ Options

Engine	Alternator	Generator Sets	Fuel System	Canopy
<ul style="list-style-type: none"> <li>•Water Jacket Preheater</li> <li>•Oil Preheater</li> </ul>	<ul style="list-style-type: none"> <li>•Winding Temperature measuring Instrument</li> <li>•Alternator Preheater</li> <li>•PMG</li> <li>•Anti-damp and anti-corrosion treatment</li> <li>•Anti-condensation heater</li> </ul>	<ul style="list-style-type: none"> <li>•Tools with the machine</li> </ul>	<ul style="list-style-type: none"> <li>• Low fuel level alarm</li> <li>•Automatic fuel feeding system</li> <li>•Fuel T-valves</li> </ul>	<ul style="list-style-type: none"> <li>•Rental Type Canopy</li> <li>•Trailer</li> </ul>
Lubricating System	Exhaust System	Cooling System	Control Panel	Voltages
<ul style="list-style-type: none"> <li>•Oil with the machine</li> </ul>	<ul style="list-style-type: none"> <li>•Protection board from hotness</li> </ul>	<ul style="list-style-type: none"> <li>• Front heat protection</li> <li>• Coolant (-30°C)</li> </ul>	<ul style="list-style-type: none"> <li>•Remote control panel</li> <li>• ATS</li> <li>• Remote controller</li> <li>• Synchronizing controller</li> </ul>	<ul style="list-style-type: none"> <li>• 415/240V</li> <li>• 380/220V</li> <li>• 220/127V</li> <li>• 220/127V</li> <li>• 200-115V</li> </ul>



## Control Panel



## Product description

- Single gen-set controller for Stand-by and Prime-power applications
- Direct communication with EFI engines
- Total remote monitoring and control

## Key features

- Easy to install, configure and use
- Wide range of communication capabilities including:
  - connection via RS232, RS485, CAN and on board USB
  - internet access using Ethernet or GPRS
  - support for Modbus and SNMP protocols
- Cloud-based monitoring and control
- Active SMS and emails in different languages
- 2x 5 A binary outputs for cranking and fuel solenoid
- Option for up to 16 additional binary inputs/outputs
- Flexible event based history with up to 350 events
- Load shedding, dummy load capability
- Automatic temperature based cooling/heating
- Comprehensive gen-set protections
- Multipurpose flexible timers
- True RMS measurement

## Available extension modules

Product	Description	Order code
CM-Ethernet	Ethernet interface	CM2ETHERXBX
CM-GPRS	GSM modem / wireless internet	CM2GPRSXXBX
CM-RS232-485	Dual port interface	CM223248XBX
EM-BIO8-EFCP	8 additional binary inputs/outputs	EM2BIO8EXBX

## Functions and protections

Description	ANSI code	Description	ANSI code
Over voltage	59	Load shedding	32P
Under voltage	27	Overload	32
Voltage asymmetry and Phase rotation**	47	Power factor	55
Over frequency	81H	Temperature	49T
Under frequency	81L	Gas (fuel) level	71
Over current*	50 + 51	Earth fault current	50N + 64
Current unbalance	46		

\* Short current only

\*\* Fixed setting

