

Model: C1250D5

Powered by CUMMINS

Output Rating

MODEL		Power rating		Voltage available
		PRIME(1)	STANDBY(2)	
C1250D5	400V/50HZ	908KW	1000KW	380/220V400/230V415/240V
	PF:0.8	1135KVA	1250KVA	


General Information

Model	C1250D5	
Engine	KTA38G9	
Speed control type	Electronic	
Phase	3	
Control System	Digital	
System voltage	24V	
Frequency	50HZ	
Engine Speed(RPM)	1500	
Fuel Consumption L/hr	Standby power(2)	256
	Prime Power(1)	296
	75% prime power	137
	50% prime power	79



Dimension and Weight

Dimension	Open	Silent
Length(L)	4400mm	6058mm
Width (W)	2100mm	2438mm
Height (H)	2250mm	2591mm
Net Weight	7800KG	13500KG



AGG POWER gensets are compliant with EC mark which include the following directives:

- * 2006/42/EC Machinery safety.
- * 2006/95/EC Low voltage
- * EN 60204-1: 2006+A1:2009, EN ISO 12100:2010, EN ISO 13849-1: 2008, EN 12601: 2010

(1) Prime Power (PRP):

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operation conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24h of operations shall not exceed 70% of the PRP.

(2) Standby Power (ESP):

According to ISO 8528-1:2005, standby power is the maximum power available during available electrical power sequence, under the stated operation conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24h of operation shall not exceed 70% of the ESP.



Engine Specification

GENERAL ENGINE DATA

Type4-Cycle; 60° Vee; 12-Cylinder Diesel
 Aspiration..... Turbocharged and Aftercooled
 Bore x Stroke.....in x in (mm x mm) 6.25x 6.25 (159 x 159)
 Displacement - in.3(L).....2300 (37.8)
 Compression Ratio13.9:1

Dry Weight

--Fan to Flywheel Engine - lb. (kg).....9482(4300)

Wet Weight

--Fan to Flywheel Engine - lb. (kg).....10002(4536)

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Block lb *ft2(N*m) 4500 (6100)

EXHAUST SYSTEM

Maximum Back Pressure..... — in Hg (mm Hg) 3 (76)

AIR INDUCTION SYSTEM

Maximum Intake Air Restriction
 with Dirty Filter Element..... in H₂O (kPa) 25 (6.2)
 with Clean Filter ElementkPa (in H₂O) 3.7 (15)

COOLING SYSTEM

Coolant Capacity - Engine Only - U.S. gal (L)..... 32.7 (124)
 - With hx 6076 Heat Exchanger - U.S. gal (L).....52.7 (199)
 Minimum Pressure Cap (for Cooling Systems with less than 2m [6 ft.] Static Head)..... — kPa (psi) 69 (10)
 Maximum Static Head of Coolant Above Engine Crank Centerline..... — m (ft) 18.3 (60)
 Thermostat (Modulating) Range — °C (°F) .. 82-93 (180-200)
 Maximum Coolant Friction Head External to Engine — 1500 rpm — kPa (psi) 48 (7)
 Maximum Top Tank Temperature for Standby..... — °C (°F) 104 (220)
 Maximum Raw Water Flow @ 90 F to HX6076 Heat Exchanger..... — liter/min (US gpm) 409 (108)
 Maximum Raw Water Inlet Pressure at HX 6076 Heat Exchanger — kPa (psi) 345 (50)

LUBRICATION SYSTEM

Oil Pressure @ Idle Speed..... — kPa (psi) 138 (20)
 @ Governed Speed..... — kPa (psi) 310-448 (45-65)
 Maximum Oil Temperature — °C (°F) 121 (250)
 Oil Capacity with OP6023 Oil Pan: Low - High..... — litre (US gal) 114-87 (30-23)
 Total System Capacity (with Combo Filter)..... — litre (US gal) 135 (35.7)

FUEL SYSTEM

Type Injection System Direct Injection Cummins PT
 Maximum Restriction at PT Fuel Injection Pump — with Clean Fuel Filter..... — mm Hg (in Hg) 102 (4.0)
 — with Dirty Fuel Filter..... — mm Hg (in Hg) 203 (8.0)
 Maximum Allowable Head on Injector Return Line (Consisting of Friction Head and Static Head)..... — mm Hg (in Hg) 165 (6.5)
 Maximum Fuel Inlet Temperature —°C (°F) 70 (160)
 Maximum Fuel Flow to Injection Pump..... — litre / hr (US gph) 428 (113)

ELECTRICAL SYSTEM

Cranking Motor (Heavy Duty, Positive Engagement).....volt 24
 Battery Charging System, Negative Ground..... --- ampere 35
 Maximum Allowable Resistance of Cranking Circuit.....ohm 0.002
 Minimum Recommended Battery Capacity
 -Cold Soak @ 50 °F(10°C) and Above.....0 °F CCA 1200
 Cold Soak @ 32°Fto 50 °C (0 °C to 10°C).....0 °F CCA 1280
 -Cold Soak @ 0 °F to 32 °C (-18 °C to 0 °C).....0 °F CCA1800



▪ Alternator

Alternator		
Poles	Num	4
Winding Connections (standard)		Star-serie
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Exciter System		Brushless
Voltage Regulator		A.V.R. (Electronic)
Bearing		Single bearing
Coupling		Flexible disc
Coating type		Standard (Vacuum impregnation)

▪ Options

Engine	Alternator	Generator Sets	Fuel System	Canopy
<ul style="list-style-type: none"> •Water Jacket Preheater •Oil Preheater 	<ul style="list-style-type: none"> •Winding Temperature measuring Instrument •Alternator Preheater •PMG •Anti-damp and anti-corrosion treatment •Anti-condensation heater 	<ul style="list-style-type: none"> •Tools with the machine 	<ul style="list-style-type: none"> • Low fuel level alarm •Automatic fuel feeding system •Fuel T-valves 	<ul style="list-style-type: none"> •Rental Type Canopy •Trailer
Lubricating System	Exhaust System	Cooling System	Control Panel	Voltages
<ul style="list-style-type: none"> •Oil with the machine 	<ul style="list-style-type: none"> •Protection board from hotness 	<ul style="list-style-type: none"> • Front heat protection • Coolant (-30°C) 	<ul style="list-style-type: none"> •Remote control panel • ATS • Remote controller • Synchronizing controller 	<ul style="list-style-type: none"> • 415/240V • 380/220V • 220/127V • 220/127V • 200-115V



Control Panel



Product description

- Single gen-set controller for Stand-by and Prime-power applications
- Direct communication with EFI engines
- Total remote monitoring and control

Key features

- Easy to install, configure and use
- Wide range of communication capabilities including:
 - connection via RS232, RS485, CAN and on board USB
 - internet access using Ethernet or GPRS
 - support for Modbus and SNMP protocols
- Cloud-based monitoring and control
- Active SMS and emails in different languages
- 2x 5 A binary outputs for cranking and fuel solenoid
- Option for up to 16 additional binary inputs/outputs
- Flexible event based history with up to 350 events
- Load shedding, dummy load capability
- Automatic temperature based cooling/heating
- Comprehensive gen-set protections
- Multipurpose flexible timers
- True RMS measurement

Available extension modules

Product	Description	Order code
CM-Ethernet	Ethernet interface	CM2ETHERXBX
CM-GPRS	GSM modem / wireless internet	CM2GPRSXXBX
CM-RS232-485	Dual port interface	CM223248XBX
EM-BIO8-EFCP	8 additional binary inputs/outputs	EM2BIO8EXBX

Functions and protections

Description	ANSI code	Description	ANSI code
Over voltage	59	Load shedding	32P
Under voltage	27	Overload	32
Voltage asymmetry and Phase rotation**	47	Power factor	55
Over frequency	81H	Temperature	49T
Under frequency	81L	Gas (fuel) level	71
Over current*	50 + 51	Earth fault current	50N + 64
Current unbalance	46		

* Short current only

** Fixed setting

